

Polyester roundslings

Code	Description
RGRS101	1000 kg roundsling - 0.5m EWL
RGRS102	1000 kg roundsling - 1 m EWL
RGRS103	1000 kg roundsling - 1.5m EWL
RGRS104	1000 kg roundsling - 2 m EWL
RGRS105	1000 kg roundsling - 2.5m EWL
RGRS106	1000 kg roundsling - 3 m EWL

Code	Description
RGRS201	2000 kg roundsling - 0.5m EWL
RGRS202	2000 kg roundsling - 1 m EWL
RGRS203	2000 kg roundsling - 1.5m EWL
RGRS204	2000 kg roundsling - 2 m EWL
RGRS205	2000 kg roundsling - 2.5m EWL
RGRS206	2000 kg roundsling - 3 m EWL

EWL = Effective Working Length

Mode factor	WLL capacity of a roundsling		
	1 ton	2 ton	
 Direct tension	1,0	1000kg	2000kg
 Choke	0,8	800kg	1600kg
 Up to 7°	2,0	2000kg	4000kg
 Over 7° up to 45°	1,4	1400kg	2800kg
 Over 45° up to 60°	1,0	1000kg	2000kg
 Over 7° up to 45°	0,7	700kg	1400kg
 Over 45° up to 60°	0,5	500kg	1000kg