



SUPPORTED TRUSS SYSTEMS

| | QL52A | QL40A |
|---------------------------|---|---|
| Main tubes | Extruded aluminium EN-AW 6082 T6 – Ø50x4 | Extruded aluminium EN-AW 6082 T6 – Ø50x4 |
| Crossways tubes | Extruded aluminium EN-AW 6082 T6 – Ø30x3 | Extruded aluminium EN-AW 6082 T6 – Ø30x3 |
| Connecting fork | Aluminium EN-AW 6082 T6 | Aluminium EN-AW 6082 T6 |
| Max height as a tower [m] | 15 | 12 |

COMPONENTS

| Description | Weight |
|--|-----------|
| MTB52 Base in sheet aluminium EN-AW 5083 – 15 mm thickness + 4 stabilizers | 217 Kg |
| MTT52F Top in aluminium alloy EN-AW 6082 T6 with four pulleys | 19 Kg |
| QL52A truss system (approx.) | 15 Kg/m |
| QL40A truss system (approx.) | 12,5 Kg/m |

These technical data are valid only for structures entirely assembled with Litec materials.

| | | |
|--------------------------------|---|----------------------------------|
| Emissione 14/04/2004 | LITEC s.r.l. – Via Venier, 52 – 30020 Marcon (VE) www.litetruss.com - info@litetruss.com | LLTCST29GB2 Versione 2 |
|--------------------------------|---|----------------------------------|